

# Learning to Generate Wire Sculpture Art from 3D Models

HuiGuang Huang  
National Cheng Kung University  
Taiwan  
604300468@qq.com

Dong-Yi Wu  
National Cheng Kung University  
Taiwan  
cutechubbit@gmail.com

Thi-Ngoc-Hanh Le  
National Cheng Kung University  
Taiwan  
ngocthanh.le1987@gmail.com

Po-Chih Chen  
National Cheng Kung University  
Taiwan  
t857057@gmail.com

Shih-Syun Lin  
National Taiwan Ocean University  
Taiwan  
catchylss@gmail.com

Tong-Yee Lee  
National Cheng Kung University  
Taiwan  
tonylee@mail.ncku.edu.tw




Figure 1: Our method transforms the input point clouds into wire sculptures that maximally preserve the original shape.

## ACM Reference Format:

HuiGuang Huang, Dong-Yi Wu, Thi-Ngoc-Hanh Le, Po-Chih Chen, Shih-Syun Lin, and Tong-Yee Lee. 2023. Learning to Generate Wire Sculpture Art from 3D Models. In *Proceedings of ACM Conference (SA '23 Posters)*. ACM, New York, NY, USA, 2 pages. <https://doi.org/XXXXXXX.XXXXXXX>

## 1 INTRODUCTION

Creating line abstractions of 3D objects without being constrained by viewing angles is a non-trivial task. Previous methods [Yang et al. 2021; Yeh et al. 2022] usually do not consider viewing angles or focus on one single view. This means that the wire sculpture has to be viewed from a certain angle to deduce the original model. Compared with optimizing the wire configuration for a single view [Yang et al. 2021], our goal is to create wire sculptures that preserve the volume of the original 3D shape by giving a user-specified template to a template-based network, e.g. an 8-vertex cube. The template provides a hard constraint on the topology. The result of our method can correctly maintain the overall structure of the 3D model regardless of the view angle.

Considering that this task poses a significant optimization challenge, in our work, we adopt the deep learning technique whit

unique ability to optimize in a very large search space. By training an end-to-end neural network, we enable the parameterized surface to fit the 3D shape's surface while preserving its topological structure. The trained model can directly predict a 3D curve representation that retains object features.

## 2 METHOD




Figure 2: Method overview.

The overview of our proposed method is shown in Figure 2. Our aim is to transform a point cloud into a wire model that accurately captures the object's volume

*Curve Generation Network.* The output of the curve generation network is a set of cubic Bézier curves derived from a three-dimensional point cloud. The entire network is an encoder-decoder architecture,

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

SA '23 Posters, December 12-15, 2023, Sydney, New South Wales, Australia

© 2023 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM... \$15.00

<https://doi.org/XXXXXXX.XXXXXXX>

which consists of two main components: the *feature extractor* and the *curve decoder*. For the feature extractor network, we utilize a neural network based on EdgeConv [Wang et al. 2019] as our building block. EdgeConv performs a convolution operation on an input point and its neighbors to obtain aggregated edge features. The decoding network, on the other hand, consists of two fully connected layers (256, 128) followed by an output layer of dimension  $3k$ , where  $k$  represents the number of control points derived from the template. For example, a simple cube has 32 control points (four control points per cubic Bézier curve minus the shared vertices.)

Given a point cloud of  $n$  points:  $\mathbf{X} = \{x_1, x_2, \dots, x_n\} \in \mathbb{R}^3$ , the entire generation network can produce a parameterized curve expressed as follows:

$$F_{\theta}^{-1} \mathbf{X}^o = \{c_0, c_1, \dots, c_{m-1}\},$$

where  $\theta$  represents learnable network parameters and  $\{c_0, c_1, \dots, c_{m-1}\}$  are  $m$  connected cubic Bézier curves segments.

**Loss function.** Our network is trained with the weight sum of three loss functions  $L_{Chamfer}$ ,  $L_{kl}$ , and  $L_{flatness}$ . The chamfer loss ( $L_{Chamfer}$ ) is to measure the distance between the fitted template and the input point cloud surface. We adopt the concept of Coons patches [Smirnov et al. 2021] to convert curve representation to surface. The other key loss function is the KL divergence for training the Variational Autoencoder. Additionally, we impose flatness loss to bias the network to generate smooth curves. The overall loss function is summarized as

$$L = L_{Chamfer} + L_{kl} + L_{flatness}$$

**Post-processing.** In this step, we convert the curves to a 3D mesh model as our final output. The curves are solidified by adding thickness to them. Toruses are used at the joint of two curves.


### 3 EXPERIMENTS

We use two datasets in our study: an animal point cloud dataset [Tulsiani et al. 2017] comprising 130 animal point clouds representing various species, and ShapeNet [Chang et al. 2015], a large-scale dataset with diverse 3D models.


We present the results generated by our method in Figure 1. Our proposed method demonstrates a good ability to retain point cloud contours from various viewpoints and effectively captures the sense of volume. Figure 3 depicts the wire art model generated from templates of different complexity. Because of our template-based approach, users can easily control the level of detail for their wire sculptures. Compared with the method that does not consider the viewing angles [Yeh et al. 2022], our result can better preserve the sense of volume. It is evident in Figure 4(a) that our result is more consistent across different views.

### 4 CONCLUSION

We propose a template-based approach for generating 3D wire art using neural networks, and it is self-supervised, requiring no labeled data. However, we observe that the structure and connections of the lines are primarily constrained by templates, limiting the complexity of the generated line structures based on the given templates, especially for toroidal or more complex models. In the



**Figure 3: Wire sculptures generated given the same input point cloud but with different templates.**



**Figure 4: (a) Comparison of our method with Yeh et al.'s. (b) Our method fails at a chair with a hole in it.**

future, we aim to enhance our method to achieve better results on complex models with genus greater than zero, for example, a chair with a hole in it in Figure. 4(b).

### ACKNOWLEDGMENTS

We thank the reviewers for their insightful comments and suggestions. This work was supported in part by the National Science and Technology Council (under nos. 111-2221-E-006-112-MY3 and 110-2221-E-006-135-MY3, 112-2221-E-019-063-MY3 and 110-2221-E-019-052-MY3), Republic of China (ROC), Taiwan.

### REFERENCES

- Angel X. Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, Jianxiong Xiao, Li Yi, and Fisher Yu. 2015. *ShapeNet: An Information-Rich 3D Model Repository*. Technical Report arXiv:1512.03012 [cs.GR]. Stanford University – Princeton University – Toyota Technological Institute at Chicago.
- Dmitriy Smirnov, Mikhail Bessmeltsev, and Justin Solomon. 2021. Learning Manifold Patch-Based Representations of Man-Made Shapes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.
- Shubham Tulsiani, Hao Su, Leonidas J. Guibas, Alexei A. Efros, and Jitendra Malik. 2017. Learning Shape Abstractions by Assembling Volumetric Primitives. In *Computer Vision and Pattern Recognition (CVPR)*.
- Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E. Sarma, Michael M. Bronstein, and Justin M. Solomon. 2019. Dynamic Graph CNN for Learning on Point Clouds. *ACM Trans. Graph.* 38, 5, Article 146 (oct 2019), 12 pages. <https://doi.org/10.1145/3326362>
- Zhijin Yang, Pengfei Xu, Hongbo Fu, and Hui Huang. 2021. WireRoom: Model-Guided Explorative Design of Abstract Wire Art. *ACM Trans. Graph.* 40, 4, Article 128 (jul 2021), 13 pages. <https://doi.org/10.1145/3450626.3459796>
- Chih Kuo Yeh, Thi Ngoc Hanh Le, Zhi Ying Hou, and Tong Yee Lee. 2022. Generating Virtual Wire Sculptural Art from 3D Models. *ACM Transactions on Multimedia Computing, Communications and Applications* 18, 2 (May 2022). <https://doi.org/10.1145/3475798>